ALPHA 1200 Sx



Power	1200 VA / 600 W
Technology	
Type	In-line
Automatic voltage regulation (AVR)	Buck + boost
Wave	
Wave form	Modified sinewave
Input	
Number of sockets	1
Type of sockets	French
Nominal voltage	230 V
Voltage range	175-285 Vac
Frequency	50 Hz
Frequency range	±3 Hz
Filtres EMI/RFI	20 kHz ~ 30 MHz
Surge protection	315 J
Fuse: amperage	5 A
Fuse: voltage	250 V
Output	
Number of UPS & Surge protected sockets	4
Type of sockets	IEC
Nominal voltage	230 Vac
Voltage range	±10%
Transfer time	<4 ms
Batteries	
Type	Etanche, plomb-acide, sans entretien
Voltage	12 V
Amperage	7 Ah
Qty	2
Back-p time	20 min
Cold start	YES
Green power function	YES
Recharge time	8 h
Display	
Type	LED
Communication	
RJ11 Connection	Tel/fax/modem/DSL
Computer connection	USB
Cables	
Cables	Included
Software	
Name	Upsilon 2000
Included / Downloadable	Included
Guarantee	
Guarantee	2 years
Insurance	
Insurance	120 000 euros
Product	
Dimensions (DxWxH)	30 x 12 x 19,5 cm
Net weight	11,00 kg
Physical	
Operative temperature	0-40 °C
Operative relative humidity	0-90%